



| | |
|-------------------------|----------------------------|
| Product Code | F 3059 |
| Product Name | JIS Storm Straight BV - 5K |
| Material Codes | GSC25 |
| Design | JIS F73059 |
| Flange And Their Joints | JIS B2220-5K |
| Tests | JIS F7400 |
| Working Pressure | 5K |
| Applications | Water and seawater systems |

| No | Part | Material |
|----|--------------|-------------------|
| 1 | Body | Cast steel GSC25 |
| 2 | Bonnet | Cast steel GSC25 |
| 3 | Packing | Neopren |
| 4 | Disc | Bronze Rg5 |
| 5 | Stem | Special brass/SUS |
| 6 | Disc lever | Bronze Rg5 |
| 7 | Weight | Lead |
| 8 | Pin | Brass |
| 9 | Gasket | Graphite |
| 10 | Gland | Bronze Rg5 |
| 11 | Glandpacking | Graphite |
| 12 | Plug | Brass |

| Valve Measures | Pressure | 5K | | | | | | | |
|----------------|-----------------|-----|--------|--------|--------|--------|--------|--------|--------|
| | Diameter | DN | 50 | 65 | 80 | 100 | 125 | 150 | 200 |
| | Valve Dimension | L | 210 | 240 | 260 | 280 | 330 | 360 | 450 |
| | | D | 130 | 155 | 180 | 200 | 235 | 265 | 320 |
| | | nxd | 4x15 | 4x15 | 4x19 | 8x19 | 8x19 | 8x19 | 8x23 |
| | | Hcd | 105 | 130 | 145 | 165 | 200 | 230 | 280 |
| | Impa Code | | 754241 | 754242 | 754243 | 754244 | 754245 | 754246 | 754247 |